


SC-22P4-4V / SC-22P8-8V

Value Express NVR



- Up to 4 MP Resolution Recording
- Up to 4 or 8 Cameras can be Connected
- H.265+/H.265/H.264+/H.264/MPEG Compression
- Plug and Play with up to 4 or 8 Independent PoE Cameras
- Up to 4 or 8 PoE Network Connections
- One SATA Interface
- Up to 6 TB Hard Drive Capacity

Value Express SC-22PX-XV NVRs feature a video output of up to 1080p. They offer full channel recording at up to 4 MP and feature H.265+ compression technology, which improves recording efficiency and reduces data storage costs.

Plug and Play technology supports up to 4 or 8 Independent PoE cameras, depending on the model.

Additionally, SC-22PX-XV NVRs support basic analytics such as Smart Search and Smart Playback, and are equipped with basic line crossing and intrusion detection capabilities.


Available models:
SC-22P4-4V
SC-22P8-8V

Specifications

	SC-22P4-4V	SC-22P8-8V
Video Input		
IP Video Input	4-ch Up to 4 MP resolution	8-ch
Network		
Incoming Bandwidth	40 Mbps	60 Mbps
Outgoing Bandwidth	60 Mbps	
Video Output		
Recording Resolution	4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
HDMI/VGA Output Resolution	1920 x 1080p, 1280 x 1024, 1280 x 720, 1024 x 768	
Decoding		
Decoding Format	H.265+/H.265/H.264+/H.264	
Live View/Playback Resolution	4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
Synchronous Playback	4-ch	8-ch
Capability	1-ch @ 4 MP/2-ch @ 1080p	
Network Management		
Network Protocols	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™	
Hard Disk		
SATA	1 SATA interface	
Capacity	Up to 6 GB capacity for each disk	
External Interface		
Network Interface	1-port RJ-45 10M/100M self-adaptive Ethernet port	
USB Interface	2 x USB 2.0	
PoE Interface		
Interface	4-port RJ-45 10/100 Mbps self-adaptive Ethernet interface	8-port RJ-45 10/100 Mbps self-adaptive Ethernet interface
Power	≤36 W	≤75 W
Standard	IEEE 802.3 af/at	
General		
Power Supply	48 VDC	
Power	≤50 W	≤90 W
Consumption (without HDD and PoE)	≤10 W	
Working Temperature	14° F to 131° F (10° C to 55° C)	
Working Humidity	10 to 90%	
Chassis	1U chassis	
Dimensions (W x D x H)	10.2" x 8.9" x 1.9" (260 mm x 225 mm x 48 mm)	
Weight (without HDD)	2.2 lbs (1.0 kg)	

Physical Interfaces

SC-22P8-8V



1. Power Supply	5. LAN Network Interface
2. VGA Interface	6. GND
3. HDMI Interface	7. Network Interfaces with PoE Function
4. USB Interface	

Note: The SC-22P4-4V has 4 network interfaces with PoE function.